



RED LINE 5W30 MOTOR OIL



- Most popular oil for modern road cars and light trucks, as specified for most late-model BMW, General Motors, and Nissan vehicles
- Suitable for VW/Audi 502.00/503.01/505.01-99, BMW LL-01 and Ford WSS-M2C946-A
- Thicker oil film at operating temperature than a petroleum 10W40

RECOMMENDED FOR:

API SN/SM/SL/CF
ACEA A3/B3/B4

AC Delco
10-9016
10-9050
19293000
88862360

Honda
08798-9034
08798-9039

BMW

07 51 0 002 545
07 51 0 017 866
07 51 0 038 678
07 51 1 469 399
LL-01
LL-98

Hyundai/Kia
05100-00410

Mini
07 51 0 143 829

Ford

WSS-M2C205-A
WSS-M2C913-A
WSS-M2C913-B
WSS-M2C913-C
WSS-M2C929-A
WSS-M2C929-B
WSS-M2C946-A
XO-5W30-QFS

Mazda
0000-77-5W30-QT

GM

12345885
294272
4718M
6094M
dexos1®

GM-LL-A-025
Mercedes Benz
MB 229.3
MB 229.5

Mopar

04761838MB
04761838PB
04761844MB
04761844PC
05166241PA
68001334PB
68169969PA
MS-9214

Mitsubishi

MZ314151
MZ320270

VW/Audi

502.00-97
503.01
505.01-99

Nissan

999MP-5W30EP

Subaru

SOA868V9280
SOA868V9285

Toyota

00279-1QT5W

dexos is a registered trademark of General Motors Corp.

TYPICAL PROPERTIES:

ACEA Service Class	A3 B3/B4
API Service Class	SN/SM/SL/CF
SAE Viscosity Grade (Motor Oil)	5W30
Vis @ 100°C, cSt	11.9
Vis @ 40°C, cSt	71
Viscosity Index	166
CCS Viscosity, Poise, @ °C	60@-30
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6
HTHS Vis, cP @150°C, ASTM D4741	3.7

PACKAGE SIZES:

- 15304 - 5W30 Motor Oil - quart
- 15305 - 5W30 Motor Oil - gallon
- 15306 - 5W30 Motor Oil - 5 gallon
- 15308 - 5W30 Motor Oil - 55 gallon

ABOUT RED LINE MOTOR OIL

- Full synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM