



RED LINE LIGHTWEIGHT SHOCKPROOF®



- Film thickness greater than an SAE 75W140, yet low fluid friction like 80W gear oil or 30W motor oil
- Excellent low-temp flow, improved cold shifting
- For racing differentials under moderate loads
- Popular in racing transmissions like Hewland and other Road Racing dog-ring boxes, Bert and Brinn for Stock Cars, G-Force and Liberty clutchless for Drag Racing

RECOMMENDED FOR:

CIRCLE TRACK
ROAD RACING
DRAG RACING
OFF ROAD
OTHER WET-SUMP SPLASH APPLICATIONS

PACKAGE SIZES:

58404 - LightWeight ShockProof Gear Oil - quart
58405 - LightWeight ShockProof Gear Oil - 1 gallon
58406 - LightWeight ShockProof Gear Oil - 5 gallon

ABOUT RED LINE SHOCKPROOF GEAR OILS

- Unique lubricant with solid microscopic particles offers low drag/high protection
- Relatively low viscosity, yet cushions gear teeth under extreme pressure
- Helps to prevent tooth breakage, resists throw-off
- Avoid use with pumps, coolers and filters as unique medium and affinity for metal can cause clogging
- Designed for wet sump transmissions and differentials with splash lubrication

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM